



M-series

MDS3024B14

M-SERIES SHORT EMERGENCY CART with Four Drawers and a Breakaway Lock

Features:

- Sturdy, uni-body steel construction
- Choice of lock options
- Heat sealed powder coat steel break-away lock bar
- Pack of 100 break-away seals
- Durable scratch resistant heat sealed powder coat finish
- Full extension drawers slides for easy access
- Body has pre-threaded accessory mounting holes
- Antimicrobial plastic top, removable
- Ergonomic side push handles can be mounted on either side
- 24" of vertical drawer space
- Cart is delivered assembled
- Industry only fully curved protective bumper
- Fully customizable drawer configurations
- Industry best 5" quiet rolling Tente® casters - 1 steering caster and 2 braking casters
- Latex free

Engineered &
Manufactured
in the U.S.



Color shown is Red. More than
20 additional colors are available.



Short Height, Standard Width, Four Drawer Emergency Cart with Breakaway Lock

Designed and built to meet the needs of today's healthcare market. Ergonomic side handles, comfort drawer pulls, expanded lock options and a standard antimicrobial top make things easier for your staff and help support your infection control initiatives. M-Series carts offer you choices.

Drawer Configuration:

- Two 3" drawers (7.6 cm), one 6" drawer (15.2 cm) and one 12" drawer (30.5 cm)
- 24.5" W x 17" D (62.2 x 43.2 cm)

Assembled Cart Dimensions:

- 37.25" H x 36.75" W x 22" D (94.6 cm H x 93.3 cm W x 55.9 cm D)
- Cart weight: 137 lbs (62.1 kg)
- Approximate shipping weight: 176 lbs (79.8 kg)
- Approximate Shipping Dims: 56" H x 37" W x 26" D (142.2 cm x 94 cm x 66 cm)

Warranty:

12-Year Manufacturer's Warranty on shipments to US and Canada, 5-Year Manufacturer's Warranty on all other International shipments. 1-Year Limited Warranty on any bought-out parts

HARLOFF
INNOVATING STORAGE FOR CARE

View similar products online at

<https://www.harloff.com/acute-care-carts/emergency-crash-carts/>

Toll Free: (800) 433-4064 • medicalsales@harloff.com
www.harloff.com • Ph: (719) 637-0300